


# **SAMPLECUT FSC-12**

### On-line sample cutter





Quality made in Germany











SAMPLECUT FSC-12

### SAMPLECUT FSC-12

### Area of application



**Principle of operation** 

### Sample cutting online – without having to stop the machine



### Customer benefits

- ✓ Takes samples from online materials
- No downtimes as a result of sampling
- Simplicity itself to operate
- Increases productivity
- Ensures a more efficient use of processing machinery

To monitor the progress of certain processes there is no alternative but to take frequent samples at the machine itself. However, this can only be done whilst the material is at a standstill or running slowly, and often leads to all manner of ambitious, sometimes absurd measures to enable the process to run continuously (nonstop batching, etc.).

With the Samplecut FSC, Mahlo offers a solution to the problem. The Samplecut FSC can be installed for example at a convenient place at the delivery end of a stenter. The pneumatics work at high pressure and press the circular blade through the material and against a counter block, all in a fraction of a second. The sample is punched out and fed via the sampling device to the operator end.

### Equipment



#### **Product highlights**

- Sampling at maximum line-speeds
- ✓ Punching in fractions of a second
- Increases the effi ciency of production machinery
- Robust, simple construction

The tried and tested Samplecut FSC appliance cuts samples from the high-speed product, and comprises in essence:

- Circular blade
  - Ø: 112,8 mm; A: 100 cm<sup>2</sup>
  - Ø: 159,6 mm; A: 200 cm<sup>2</sup>
- Pneumatic unit
- Sample chute
- Control panel
- Switch panel

### **Control element**


The operator need only press a button to release the sample via the control panel.





### **TECHNICAL DATA**

Angabe	Wert	Einheit
Measuring principle	Fixed sample cutter	
Size Samples	100 200	Cm <sup>2</sup>
Power supply	230 / 400	VAC
Line frequency	50 / 60	Hz
Power supply	5 - 45	°C

### Dimensions







Samplecut FSC-12 (91-014654-006)



Monitoring and control systems, automation:

# MAHLO ENSURES QUALITY. WORLDWIDE, IN YOUR VICINITY.

Best-possible technical support and know-how transfer are written in capital letters at Mahlo. Thanks to an international network of agencies and service centres, customers have at their disposal competent support worldwide. We are there for you 365 days a year, 24 hours a day. Just get in touch with us!

- ✓ Over 40 service centres worldwide
- ✓ Service partners in over 100 countries \_\_\_\_\_ Direct service and spare parts delivery
- within 24 hours
- ✓ Remote diagnostic system
- ✓ Service hotline: +49-180-5062456





#### Mahlo GmbH + Co. KG - Germany

Donaustr. 12 93342 Saal / Donau Telephone: +49-9441-601-0 Fax: +49-9441-601-102 Email: info@mahlo.com

### 21020 Daverio

Via Fiume 62

Mahlo Italia S.R.L. - Italy

Telephone: +39-0332-94-95-58 Fax: +39-0332-94-85-86 Email: mahlo.italia@mahlo.com Mahlo America Inc. - USA 575 Simuel Road Spartanburg S.C. 29304 Telephone: +1-864-576-62-88 Fax: +1-864-576-00-09 Email: mahlo.america@mahlo.com

#### Mahlo Ouest S.P.R.L. - Belgium

Quartum Center Hütte 79 - Bte 10 4700 Eupen Telephone: +32-87-59-69-00 Fax: +32-87-59-69-09 Email: mahlo.ouest@mahlo.com

### Mahlo España S.L. - Spain

Calle Luxemburgo nº 4 08303 Mataró (Barcelona) Telephone: +34-938-640-549 Email: mahlo.espana@mahlo.com

## WWW.MAHLO.COM

Samplecut FSC-12 84-010298, 1, en\_GB 06/2018 Subject to revision! © 2018 Mahlo GmbH + Co. KG



Quality made in Germany